

# How To Guide: SATIN FINISH

## STEPS:

Satin Finish is a durable, medium-duty, brush-on finish top coat.

1. Stir well before use.
2. Make sure any solids that have settled to the bottom of the container have been reincorporated into the solution.
3. It should be applied over dry, painted surfaces in a thin, even coat with a fine foam brush. Remove any pooled product.
4. If you apply the product too thickly, it will dry with a milky haze.
5. Allow each layer to dry completely (3-4 hours) prior to application of the next layer.
6. Satin Finish is non-yellowing. If you desired an aged appearance, we suggest you use our Clear Glaze tinted under the Satin Finish to achieve the desired antiqued effect.
7. Satin Finish needs one week to fully cure.

## PRO TIPS:

For ease of application, Satin Finish can be applied diluted with approximately 25% water, using several light coats to achieve a durable finish. For a hand-waxed feel, after final coat of Satin Finish has dried completely, you may apply Clear Wax or Waxing Cream on top of the Satin Finish. Give your piece a light sanding with Kraft paper or very high grit sand paper, then wax. This product requires several weeks to fully cure. Freshly finished surfaces should be kept free of moisture and heavy objects for several weeks.

Protect your finished surface from strong acids, oxidizers and grease.

Store and use between 55° - 95° degrees F.